

Paslode[®]

tetraGRIP[™]

STUDLESS SIDING SYSTEM



INSTALLS 20% FASTER ON AVERAGE*

NO MARKING STUDS > FEWER CUTS > LESS WASTE

**SECURELY FASTENS FIBER CEMENT SIDING DIRECTLY TO
OSB SHEATHING, FASTENING TO STUD NOT REQUIRED**

tetraGRIP™

STUDLESS SIDING SYSTEM

Save an average of 20%* by eliminating the time needed to locate and mark studs, and to measure and cut planks to land on studs. Fastening fiber cement siding directly to OSB with the patented 1-1/8" fastener helps prevent unintended damage to utilities behind sheathing and more importantly may increase your crew's productivity allowing you to take on more jobs per year.

- NO MARKING AND HITTING STUDS
- LESS MEASURING
- LESS CUTTING
- LESS WASTE
- LESS RISK OF CALLBACKS

WHY IT WORKS BETTER



ROTATION BONDS NAIL TO WOOD

Mechanically bonds with the wood fibers for superior holding power.

STRONG NON-DESTRUCTIVE WOOD INTERACTION

Efficient rotation helps eliminate wood destruction common in standard ring shank nails.

SUPERIOR WITHDRAWAL RESISTANCE

The barbed helix-to-wood engagement creates a high load capacity and does not require a nail-to-stud interaction.

tetraGRIP™

STUDLESS SIDING SYSTEM

FASTENER SPECIFICATIONS

Part Number: 650964
Fastener Finish: Galvanized Steel
Shank Diameter: 0.117"
Length: 1-1/8"
Head Size: Full Round Head - 0.300"
Collation Media: Plastic Coil
Shank Type: Barbed Helix
Nails Per Coil: 120
Nails Per Box: 3,600

TOOL SPECIFICATIONS

Part Number: 515400
Model Number: TG100CSN
Weight: 4.9lbs (2.2kg)
Height: 11.5"
Length: 12.25"
Width: 6"
Magazine Type: Coil
Nail Capacity: 120 Nails/Coil
Operating Pressure P.S.I. Bar: 90 - 120 PSI



Paslode

REPUTATION IS EVERYTHING™

PASLODE.COM

PASLODE® | GLENVIEW, IL 60025 | #50086



Manufactured using ITW's WERCS™ Tooling



Designed and Made in the USA